



LEOPARD SERIES - HI MILEAGE



John Deere T8000-series Guiding GE 6" - Track Length 324"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
16"x54x6" Leopard (GE 6")	16	6"	2,25" -->2,5"	948 sq. in.	11.1 psi	GE	6"	4,0"	5,9"	3,5"	1,25"	1"	4
18"x54x6" Leopard (GE 6")	18	6"	2,25" -->2,5"	1,067 sq. in.	9.8 psi	GE	6"	4,0"	5,9"	3,5"	1,25"	1"	4
24"x54x6" Leopard (GE 6")	24	6"	2,25" -->2,5"	1,423 sq. in.	7.4 psi	GE	6"	4,0"	5,9"	3,5"	1,25"	1"	4
30"x54x6" Leopard (GE 6")	30	6"	2,25" -->2,5"	1,778 sq. in.	5.9 psi	GE	6"	4,0"	5,9"	3,5"	1,25"	1"	4
John Deere T9000-series Guiding GQ 6" - Track Length 378"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
30"x63x6" Leopard (GQ 6")	30	6"	2,25" -->2,5"	2,218 sq. in.	7.5 psi	GQ	6"	5,0"	7,3"	4,2"	1,25"	1"	4
36"x63x6" Leopard (GQ 6")	36	6"	2,25" -->2,5"	2,661 sq. in.	6.3 psi	GQ	6"	5,0"	7,3"	4,2"	1,25"	1"	4
CAT/Claas 35/45/55 Guiding GF 6" - Track Length 318"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
16"x53x6" Leopard (GF 6")	16	6"	2,25" -->2,5"	916 sq. in.	9.6 psi	GF	6"	3,3"	4,7"	4,0"	1,25"	1"	4
18"x53x6" Leopard (GF 6")	18	6"	2,25" -->2,5"	1,022 sq. in.	8.6 psi	GF	6"	3,3"	4,7"	4,0"	1,25"	1"	4
24"x53x6" Leopard (GF 6")	24	6"	2,25" -->2,5"	1,375 sq. in.	6.4 psi	GF	6"	3,3"	4,7"	4,0"	1,25"	1"	4
30"x53x6" Leopard (GF 6")	30	6"	2,25" -->2,5"	1,703 sq. in.	5.1 psi	GF	6"	3,3"	4,7"	4,0"	1,25"	1"	4
CAT/Claas 65/70/75/85/95 Guiding GR 6" - Track Length 336"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
24"x56x6" Leopard (GR 6")	24	6"	2,25" -->2,5"	1,712 sq. in.	8.0 psi	GR	6"	1,5"	4,0"	4,9"	1,25"	1"	4
30"x56x6" Leopard (GR 6")	30	6"	2,25" -->2,5"	2,121 sq. in.	6.4 psi	GR	6"	1,5"	4,0"	4,9"	1,25"	1"	4
AGCO/CAT Challenger MT700-series Guiding GS 6" - Track Length 348"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
16"x58x6" Leopard (GS 6")	16	6"	2,25" -->2,5"	1,023 sq. in.		GS	6"	3"	5"	4,7"	1,25"	1"	5
18"x58x6" Leopard (GS 6")	18	6"	2,25" -->2,5"	1,140 sq. in.		GS	6"	3"	5"	4,7"	1,25"	1"	5
24"x58x6" Leopard (GS 6")	24	6"	2,25" -->2,5"	1,534 sq. in.		GS	6"	3"	5"	4,7"	1,25"	1"	5
30"x58x6" Leopard (GS 6")	30	6"	2,25" -->2,5"	1,901 sq. in.		GS	6"	3"	5"	4,7"	1,25"	1"	5
AGCO/CAT Challenger MT800-series Guiding GT 6" - Track Length 396"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
30"x66x6" Leopard (GT 6")	30	6"	2,25" -->2,5"	2,360 sq. in.		GT	6"	4"	6"	5"	1,25"	1"	5
36"x66x6" Leopard (GT 6")	36	6"	2,25" -->2,5"	2,832 sq. in.		GT	6"	4"	6"	5"	1,25"	1"	5



TIGER SERIES - HI TRACTION

John Deere T8000-series Guiding GE 4,5" - Track Length 324"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
25"x36x9" Tiger (GE 4,5")	25	9"	2,5" --> 3"	1,246 sq. in.	7.1 psi	GE	4,5"	4,0"	5,9"	3,5"	1,5"	1,25"	5
30"x36x9" Tiger (GE 4,5")	30	9"	2,5" --> 3"	1,495 sq. in.	5.9 psi	GE	4,5"	4,0"	5,9"	3,5"	1,5"	1,25"	5
John Deere T9000-series Guiding GQ 4,5" - Track Length 378"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
30"x42x9" Tiger (GQ 4,5")	30	9"	2,5" --> 3"	1,865 sq. in.	7.5 psi	GQ	4,5"	5,0"	7,3"	4,2"	1,5"	1,25"	5
CAT/Claas 35/45/55 Guiding GF 4,5" - Track Length 318"/320"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
25"x36x9" Tiger (GF 4,5")	25	9"	2,5" --> 3"	1,204 sq. in.	6.2 psi	GF	4,5"	3,3"	4,7"	4,0"	1,5"	1,25"	5
30"x36x9" Tiger (GF 4,5")	30	9"	2,5" --> 3"	1,445 sq. in.	5.1 psi	GF	4,5"	3,3"	4,7"	4,0"	1,5"	1,25"	5
CAT/Claas 65/70/75/85/95 Guiding GR 4,5" - Track Length 336"/338"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
25"x38x9" Tiger (GR 4,5")	25	9"	2,5" --> 3"	1,499 sq. in.	7.7 psi	GR	4,5"	1,5"	4,0"	4,9"	1,5"	1,25"	5
30"x38x9" Tiger (GR 4,5")	30	9"	2,5" --> 3"	1,799 sq. in.	6.4 psi	GR	4,5"	1,5"	4,0"	4,9"	1,5"	1,25"	5
AGCO/CAT Challenger MT700-series Guiding GS 4,5" - Track Length 351"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
25"x39x9" Tiger (GS 4,5")	25	9"	2,5" --> 3"	1,344 sq. in.		GS	4,5"	3"	5"	4,7"	1,5"	1,25"	6
30"x39x9" Tiger (GS 4,5")	30	9"	2,5" --> 3"	1,613 sq. in.		GS	4,5"	3"	5"	4,7"	1,5"	1,25"	6
AGCO/CAT Challenger MT800-series Guiding GT 4,5" - Track Length 396"													
SIZE	Profile				Static ground pressure (*)	Guiding					Carcass		Plies
	Width	Pitch	Depth	Pos. Cont. Area		Type	pitch	O.G.T.	O.G.B.	G.H.	middle	side	
30"x44x9" Tiger (GT 4,5")	30"	9"	2,5" --> 3"	1,984 sq. in.		GT	4,5"	4"	6"	5"	1,5"	1,25"	6

30" wide tracks cannot be used on the following CAT tractors (narrow gauge, centre to centre undercarriage measures 84,65"):



- Challenger 65 (S/N: 7YC1-1899)
- Challenger 65B (S/N: 7YC1900-UP)
- Challenger 75 (S/N: 4CJ)
- Challenger 65C (S/N: 2ZJ1-499)
- Challenger 75C (S/N: 4KK1-499)